



Sound Level Calibrator

Model DSL 336

Features :

1. 94dB and 114dB Sound Calibration at 1KHz
2. Accurate and Simple to use
3. Fits 1 inch, 1/2 inch or 1/4 inch diameter microphone

Specifications:

- DSL 336 Specifications:
 - Specifications for DSL 336 CE Approved
 - Output Sound Pressure Levels 114dB and 94dB re 20 uPa under reference conditions.
 - Output Frequency 1000Hz 4%
 - Reference Conditions TEMPERATURE -->23oC(73oF)
 - ATMOSPHERIC PRESSURE -->1013 mbar (760mm of Hg)
 - RELATIVE HUMIDITY -->65%
 - Accuracy of Sound Pressure Level Under stated reference environment conditions 0.5dB
 - Power One 9V battery 006P or IEC 6F22 or NEDA 1604.
 - Battery Test Internal circuitry checks condition of battery continuously.
 - Calibrator will operate at all if battery voltage falls below acceptable range.
 - Battery life About 50 hours
 - Dimensions 103(L) x 63(W) x 54(H)mm

สนใจติดต่อ บริษัท เอเม็ท จำกัด 11/13 หมู่ 5 ถ.สุขคนธสวัสดิ์ แขวงลาดพร้าว เขตลาดพร้าว กทม. 10230

โทร.02-9079421-2 , 02-9077480-3, แฟกซ์ : 02-9079878 , Email : sales@amet.net , Web: www.amet.net



- Weight approx. 200g (include batteries)
- Operating temperature 0 - 50oC(32 - 122oF)
- Operating humidity 0 - 90%RH
- Accessories 9V battery, Carrying case , Instruction manual. 1" ,1/2" and 1/4"
- Microphone Adaptor